


技术数据


电气连接	接插件, M12 × 1
轴轴向负载能力	20 N
轴径向负载能力	40 N
环境条件	
工作温度	-40...+85 °C
抗震动性(EN 60068-2-6)	300 m/s ² , 10...2000 Hz
抗冲击性(EN 60068-2-27)	2500 m/s ² , 6 ms
防护等级	IP67
防护等级 (轴型 / 轴套)	IP67

附件


RCS-15-06-06	1545362
波纹管联轴器外径：15 mm，孔径： 6 mm/6 mm	




RCS-15-08-06	1545361
波纹管联轴器外径：15 mm，孔径： 8 mm/6 mm	




RA-BC-20-06-06	100048777
带铝制轮毂的波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 6 mm	




RA-BC-20-06-08	100048778
带铝制轮毂的波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 8 mm	




RA-BC-20-06-10	100048779
带铝制轮毂的波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 10 mm	




RA-BC-E-20-06-06	100048785
不锈钢波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 6 mm	




RA-BC-E-20-06-10	100048786
不锈钢波纹管联轴器Ø 20 mm；d1 = 6 mm，d2 = 10 mm	




RA-SDC-30-06-10	100048791
弹性盘联轴器Ø 30 mm，d1 = 6 mm，d2 = 10 mm	



RA-SDC-30-06-06	100048790
弹性盘联轴器Ø 30 mm，d1 = 6 mm，d2 = 6 mm	




RA-HC-25-06-06	100048794
铝制螺旋联轴器Ø 25 mm；d1 = 6 mm，d2 = 6 mm	



RA-HC-25-06-10

100048795

铝制螺旋联轴器Ø 25 mm ; d1 = 6 mm , d2 = 10 mm



附件

尺寸图	型号	货号	
	RKC5701-5M	6931034	CAN (DeviceNet、CANopen) 总线线缆，M12母头接插件，直式，线缆长度5 m，护套材质PUR，煤灰色；cULus认证

